

SignGrass® Fibrisport

Fibrillated

Yarn Characteristics

Type	Polyethylene Fibrillated / Tape Slide
DTex	8.800/11.000

Tuft Characteristics

Pile Height	15 - 60 mm (margin +/- 2%)
Stitch Rate	150 - 220
Gauge	5/16" 3/8"
Tuft Lock	2 kg

Backing Characteristics

Primary Backing	Polyethylene and Woven Polyester
Secondary Backing	Latex
Water permeability	Drainage holes on request

Total Product Weight

2500 g/sqm, dependent on pile height and stitch rate

Warranty

5 year warranty against discoloration and UV light degradation.

5 year product warranty against fibers coming off.

SIGNGRASS®
synthetic grass design

Logo/Design

For the production of your logo or design, a Vector file is required. With preference .eps or .ai file.

Besides a square or rectangle mat, we can also tuft the shape of a logo or design like a circle, ellipse, hexagon or crest.

Margin total size logo mat +/- 2%

Guidelines Logo/Design

Letters, signs and logos need to be legible and feasible, so please take following guidelines in account:

Product	Fibri 24 mm (5/16" gauge)
Minimum height letter	8 - 10 cm
Detail (width)	1.0 cm
Space in between letters	1.0 cm

Possibilities


















It's possible to supply us with your own yarn, under the condition a production test is permitted.

We require a technical datasheet and sample of the artificial grass.

There is no maximum size. Logo mats larger than 12 x 4 meters will consist out of multiple parts of which the joints need to be glued on location.

SignGrass® Fibrisport

Standard colours available:

	F1 - white
	F11 - grey
	F2 - black
	F22 - vegas gold
	F6 - bright yellow
	F3 - straw yellow
	F4 - orange
	F7 - clear red
	F26 - rose pink
	F5 - red clay
	F24 - brown
	F23 - purple
	F13 - bright blue
	F8 - reflex blue
	F21 - lime green
	F9 - olive green
	F10 - field green

Other colours on request.*

* Colours may differ from the original. Also, a minor colour deviation per production batch can not be excluded.

SignGrass® Fibrisport

Fibrillated

Installation & Maintenance

Our logo mats should only be installed by a professional in order to ensure the best result.

Seams have to be secured with polyurethane special adhesive for synthetic grass.

Signgrass® logo mats are low in maintenance, just like artificial grass, but not maintenance-free!

- Brush the grass regularly with a stiff broom or rake
- Keep the grass free of debris and leaves
- Remove leaves using a leaf blower or rake
- Remove any weeds immediately to prevent seed dispersal
- Use clean water to rinse off any spills, such as liquids, sauce or melted ice-cream
- Pet excrement or smells can be removed using a shovel or detergent and water
- Avoid contact with hot materials (or close proximity to glass structures) to prevent shrinkage of the grass fibers.

Gas fading

The discolouring of polyethylene is a phenomenon that is well-known in polymer industry. It is also described as yellowing, pinking or gas fading. The colour changes of the material are generally a result of auto-oxidation of phenolic antioxidants in the basic polymer used. These phenolic antioxidants are added to the resin by the producer to protect and stabilize the polymer during processing and use. The change in colour of the polymer is strictly cosmetic and does not affect physical properties.

The sources of discoloration in polyethylene are diverse and can vary from packaging to inappropriate material composition. The most relevant source is excessive levels of atmospheric pollutants like nitrogen oxides (NOx). The relatively high levels of NOx are usually caused by exhaust gasses (gas fading), for example fork lift trucks and heaters in warehouses.

To reverse and remove the discolorations expose the material to UV-light (sunlight).

With respect to synthetic turf fibres, the yellow shine of white yarn will disappear after installation of an outside pitch. When using synthetic turf for an inside application, exposure to sunlight before installation will remove the yellow shine.



Stökskesweg 9B 5571 TJ Bergeijk The Netherlands

T +31 (0)497 5725 45 — E info@signgrass.com — I www.signgrass.com

F1 - White

F5 - Red Clay

F11 - Grey

F24 - Brown

F2 - Black

F23 - Purple

F22 - Vegas Gold

F13 - Bright Blue

F6 - Bright Yellow

F8 - Reflex Blue

F3 - Straw Yellow

F21 - Lime Green

F4 - Orange

F9 - Olive Green

F7 - Clear Red

F26 - Rose Pink

F10 - Field Green